

NON-CORRODABLE TANK HEATERS

Flat model:


Power (kW)	Profile /Shape	Thickness (mm)	low		high	
			Width (mm)	Height (mm)	Width (mm)	Height (mm)
0.5	round	25	292	292	0	0
1	round	25	292	292	0	0
1.5	low or high	25	445	292	292	445
2	low or high	25	445	292	292	445
3	low or high	25	445	292	292	445
4	low or high	50	445	292	292	445
4	square	25	445	445	0	0
4.5	low or high	50	445	292	292	445
6	low or high	50*	445	292	292	445
9	low or high	75	445	292	292	445
12	square	75	445	445	0	0
12	low or high	50	573	418	418	573
15	low or high	75	573	418	418	573
18	low or high	75	573	418	418	573



High profile



Low profile



Square



Round

* 6KW THREE PHASE: 75mm thick

Single phase 220V-240V, three phase 380V-415V, non-corrodible lead 1'5m standard, 3,5,8,12m available on most models. Thicknesses exclude hanging brackets, standoff and baffles. The heater is designed to operate continuously at temperatures up to 100°C.

Certifications: UL (USA), CE (Europa), BS EN ISO 60519/60335 (UK)

Cylindrical model:

Power (kW)	0.5	1	1.5	2	3	4
Length (mm)	145	222	325	460	670	920
Diameter (mm)	80	80	80	80	80	80
Voltage (single phase)	230V	230V	230V	230V	230V	230V



Disponibile con lunghezze di cavo de 1'5m, 3m, 5m y 8m, para medidas mas largas contacte con nosotros.

Certificación UL (USA), CE (Europa), BS EN60519-1:2003 · EN60519-2:2006 · EN60335-1:2002/A2:2006 · EN60335-2-73:2003/A1:2006 (UK)